



**AIR DATA ACCESSORIES KIT
MODEL No. ADAP8A-723
BOEING P8A AIRCRAFT
NSN: 4920-20-007-7155**

- Proprietary Information -

This kit contains all the equipment required to test from source the complete pitot and static air data system on the Boeing P8A aircraft, as well as the means of pre-testing all adaptors and hoses prior to being fitted to the aircraft.

Pitot Test Adaptor

Part No. P22399HT-3 (3 req'd.)

These units fit pitot probes 0856AE19 located on the nose of the aircraft and when installed will test each system separately and simultaneously.

Pre-Test Probe

Part No. PT421-2399 (3 req'd.)

When it becomes necessary to test the integrity of the pitot test adaptors and/or hoses and test set, these units are installed into the pitot test adaptors thus simulating the pitot head.

Elevator Feel Test Adaptor

Part No. P75701HT-4 (2 req'd.)

Pre-Test Probe

Part No. PT17570 (2 req'd.)

NSN: 4920-20-008-5035

When it becomes necessary to test the integrity of the elevator feel test adaptors and/or hoses and test set, these units are installed into the adaptors thus simulating the probe head.

Static Test Adaptor

Part No. 33410LH-125-4 (6 req'd.)

NSN: 4920-20-005-0408

Six units are supplied with this kit. To install, depress plunger into the center hole and release plunger. A slight rotating motion in each direction ensures a good seal. This unit is self-sealing, locking, aligning and testing. The protective cap on the mandrel doubles as a pre-test unit. When using as a blanking adaptor, ensure that the blanking cap is tightened before installation.

The first dash number identifies the size of hole in the center of the static vent and the last dash number identifies the fitting size (-4 indicates 1/4" hose size)

Pitot Test Hose Assembly

Part No. P8A-133 (3 req'd.)

Three of these assemblies are included in the kit and are connected to the pitot test adaptor from the designated outlet on the control console and may be selected as required.

Hoses are colour coded at each end.

Pitot Input Hose Assembly

Part No. P8A-214-H (1 req'd.)

This assembly is used to connect the pitot outlet of the pneumatic generator to the pitot inlet located on the right hand side of the control console.



**AIR DATA ACCESSORIES KIT
MODEL No. ADAP8A-723
BOEING P8A AIRCRAFT
NSN: 4920-20-007-7155**

- Proprietary Information -

Vacu-Grip Assembly

Part No. 421-8971 (1 req'd.)

One of these units is supplied with each kit to provide a means of support for static systems test hose assemblies.

Pitot & Static System Control Console

Part No. 421-737-678 (1 req'd.)

This unit contains all necessary inlets and outlets required to connect the pneumatic generator and the adaptors and hoses to the aircraft sensing system. An instant acting control valve is supplied for each outlet. These valves are shut off when the handle is in the vertical position. The static systems input and output connections and control valves are located on the left side panel whilst the pitot system connection and control valves are located on the right side. All inlets etc. are identified on the photo etched panel. A facility for testing two pairs of static adaptors simultaneously is provided on the top panel. The hoses connected to console and adaptors are color coded at each end for easy system identification.

Lubricating Fluid

Part No. LF5050 (1 req'd.)

NSN: 9150-21-920-6522

This fluid is used to lubricate the glands of the pitot test adaptor. It is recommended that a small amount be placed on the glands before installing the adaptor on pitot probe.

Static Test Hose Assembly

Part No. P8A-212 (2 req'd.)

Two of these assemblies are supplied with this kit.

Static Input Hose Assembly

Part No. P8A-111-H (1 req'd.)

This assembly is used to connect the alternate static and left and right D.A.D.C. connections to a source of vacuum (or pressure) should it become necessary to test lines of these systems simultaneously.

Alternate Static Test Hose Assembly

Part No. P8A-105 (1 req'd.)

This hose is connected to the alternate static outlet on the control box is supplied with its own separate vacuum source which can be shut off from the front of the panel. The 33410LH-125-4 adaptor is connected thereto and the adaptor to blank off the opposite side of the aircraft is also stowed in the case cover.

Reducer Hose Assembly

Part No. A352-4-6 (1 req'd.)

NSN: 4720-20-005-1768

As need be, this accessory provides for interface with an ADTS that is equipped with a -6 Static connection.



**AIR DATA ACCESSORIES KIT
MODEL No. ADAP8A-723
BOEING P8A AIRCRAFT
NSN: 4920-20-007-7155**

- Proprietary Information -

Seal Kit - Part No. SK2399HT (3 req'd.)

Three sets of spare seals (high temp) for pitot test adaptor - P/N. P22399HT-3 are stowed in the case.

Seal Kit - Part No. SK701M2 (2 req'd.)

Two sets of spare seals (high temp) for elevator feel adaptor - P/N. P75701HT-4 are stowed in the case.

Seal - Part No. 334-7 (3 req'd.)

NSN: 5330-21-903-3398

Three spare seals for static test adaptors - P/N. 33410LH-125-4 are stowed in the case.

Manual - Part No. 444-P8A-723

One manual is supplied with each kit.

The equipment is enclosed in case assembly.